

HORSESHOE BOLLARD

Our SlowStop® Horseshoe Bollards have twice the stopping power of our single rebounding bollards. They consist of two rebounding bollard bases with steel pipe and connectors to create a horseshoe bollard. This is ideally suited to protect confined areas.


3" Rebounding Horseshoe Bollard Kit (36"H x 36"W)

Part No. SS3Y-36-HS-36



Recommended Uses: Column protection, pedestrian protection, rack and equipment guarding, access denial, post-tensioned concrete.

Color:	RAL 1018 Yellow Bollard on Black Base
Diameter:	3" (2.5" ANSI Schedule 40)
Dimensions:	36" Height x 36" Width
Product Weight	97 lbs
Energy Absorption:	3,240 joules / 2,390 ft-lb
Temperature Rating:	-40°
Pipe Coating:	150µm Polyester Outdoor Power Coat
Cast Iron Coating:	Environmentally Friendly Water-Based KTL Coating
Set Screws:	M12 x 2.00mm Hex
Anchor Screws:	(8) 5/8" x 5-1/2" Concrete Anchor Screws



4" Rebounding Horseshoe Bollard Kit (28" H x 36"W)

Part No. SS4Y-28-HS-36



Recommended Uses: Fuel pump protection, equipment & storage rack guarding, drive-thru lanes, utility protection, access denial, post-tensioned concrete.

Color:	RAL 1018 Yellow Bollard on Black Base
Diameter:	4" (3.5" ANSI Schedule 40)
Dimensions:	28" Height x 36" Width
Product Weight	154 lbs
Energy Absorption:	5,334 joules / 3,934 ft-lb
Temperature Rating:	-40°
Pipe Coating:	150µm Polyester Outdoor Power Coat
Cast Iron Coating:	Environmentally Friendly Water-Based KTL Coating
Set Screws:	M16 x 2.00mm Hex
Anchor Screws:	(8) 5/8" x 5-1/2" Concrete Anchor Screws

4" Rebounding Horseshoe Bollard Kit (42" H x 36"W)

Part No. SS4Y-42-HS-36



Recommended Uses: Gas pump protection, equipment & storage rack guarding, drive-thru lanes, utility protection, access denial, post-tensioned concrete.

Color:	RAL 1018 Yellow Bollard on Black Base
Diameter:	4" (3.5" ANSI Schedule 40)
Dimensions:	42" Height x 36" Width
Product Weight	165 lbs
Energy Absorption:	5,334 joules / 3,934 ft-lb
Temperature Rating:	-40°
Pipe Coating:	150µm Polyester Outdoor Power Coat
Cast Iron Coating:	Environmentally Friendly Water-Based KTL Coating
Set Screws:	M16 x 2.00mm Hex
Anchor Screws:	(8) 5/8" x 5-1/2" Concrete Anchor Screws

Custom Modular Fencing Solutions

Pipe-Per -Foot Available



Do you need a custom shape or size? With our SlowStop® Connectors, the possibilities are nearly endless. Contact us today for a quote on custom arrangements.

3" Pipe-Per-Foot	Part # SS3Y-PIPE-XX
4" Pipe-Per-Foot	Part # SS4Y-PIPE-XX
5" Pipe-Per-Foot	Part # SS5Y-PIPE-XX
6" Pipe-Per-Foot	Part # SS6Y-PIPE-XX

EDGE Fall Protection, LLC

SLOWSTOP CONNECTORS

The SlowStop® connector system allows you to build fencing and cross posts without the need for welding pipe. Simply slide the pipe into the connector and tighten the special set-screws. Multiple bases connected together greatly increase the stopping power of the SlowStop® System.

3" Elbow Connector

Part No. SS3-ELBOW



Elbow connector for 3" SlowStop® pipe. Our Elbow Joint is made of the same tough nodular cast iron as our SlowStop® bases. Hardware Included.

Color:	Black
Diameter:	3" (2.5" ANSI Schedule 40)
Dimensions:	Height: 7.0" x Width: 7.0"
Product Weight	12 lbs
Temperature Rating:	-40°
Material:	Cast Iron
Set Screw:	(12) M12 x 2.00mm Hex

3" Tee Connector

Part No. SS3-TEE



Tee connector for 3" SlowStop® pipe. Our Tee Joint is made of the same tough nodular cast iron as our SlowStop® bases. Hardware Included.

Color:	Black
Diameter:	3" (2.5" ANSI Schedule 40)
Dimensions:	Height: 6.3" x Width: 7.8"
Product Weight	12 lbs
Temperature Rating:	-40°
Material:	Cast Iron
Set Screw:	(18) M12 x 2.00mm Hex


3" Cross Connector

Part No. SS3-CROSS



Cross connector for 3" SlowStop® pipe. Our Cross Joint is made of the same tough nodular cast iron as our SlowStop® bases. Hardware Included.

Color:	Black
Diameter:	3" (2.5" ANSI Schedule 40)
Dimensions:	Height: 9.1" x Width: 7.9"
Product Weight	15 lbs
Temperature Rating:	-40°
Material:	Cast Iron
Set Screw:	(24) M12 x 2.00mm Hex



4" Elbow Connector

Part No. **SS4-ELBOW**



Elbow connector for 4" SlowStop® pipe. Our Elbow Joint is made of the same tough nodular cast iron as our SlowStop® bases. Hardware Included.

Color:	Black
Diameter:	4" (3.5" ANSI Schedule 40)
Dimensions:	Height: 9.6" x Width: 9.6"
Product Weight	21 lbs
Temperature Rating:	- 40°
Material:	Cast Iron
Set Screw:	(12) 5 M16 x 2.00mm Hex

4" Tee Connector

Part No. **SS4-TEE**



Tee connector for 4" SlowStop® pipe. Our Tee Joint is made of the same tough nodular cast iron as our SlowStop® bases. Hardware Included.

Color:	Black
Diameter:	4" (3.5" ANSI Schedule 40)
Dimensions:	Height: 9.1" x Width: 10.13"
Product Weight	22 lbs
Temperature Rating:	- 40°
Material:	Cast Iron
Set Screw:	(18) 5 M16 x 2.00mm Hex

4" Cross Connector

Part No. **SS4-CROSS**



Cross connector for 4" SlowStop® pipe. Our Cross Joint is made of the same tough nodular cast iron as our SlowStop® bases. Hardware Included.

Color:	Black
Diameter:	4" (3.5" ANSI Schedule 40)
Dimensions:	Height: 13.25" x Width: 10.13"
Product Weight	29 lbs
Temperature Rating:	- 40°
Material:	Cast Iron
Set Screw:	(24) 5 M16 x 2.00mm Hex